

Krystal-X Easy

USB-powered digital CCD sensor

Digital imaging in all simplicity



CCD sensor

Krystal-X Easy Digital imaging in all simplicity

High definition at reduced dose.

Thanks to leadingedge technology that
combines a leaded
fibre optic plate,
a high resolution
CCD and a new CSI
scintillator screen,
the Krystal-X is
capable of acquiring
high resolution
quality images
at low doses.

A portable system

The new Krystal-X Easy sensor has been conceived to be integrated with your X-ray generator, while maintaining the possibility to quickly move it from one operatory to another. Thanks to its wall mount and integrated sensor support, the practitioner can move the Krystal-X Easy system in a quick and easy way and retain perfect working ergonomics.

Enhanced ergonomics

The Krystal-X is manufactured using a leading edge industrial process, which meets the most stringent requirements with regards to strength, waterproof qualities and handling comfort such as the rounded edges of the sensor.



A versatile system

- The Krystal-X Easy system uses a USB 2.0 High Speed connection, but is also compatible with USB 1.1 Full Speed. The intra oral sensor is available in two sizes (600 mm² or 816 mm²).

TECHNICAL SPECIFICATIONS	
Technology	CCD + fibre optics + CSI scintillator
Theoretical CCD resolution	26,3 lp/mm
True sensor resolution	> 20 lp/mm
Active area	30 mm x 20 mm (600 mm²), 34 mm x 24 mm (816 mm²)
USB standard	USB 2.0 High Speed (480 Mbit/s) and USB 1.1 Full Speed (11 Mbit/s)
Norms	NF EN 60601-1 / NF EN 60601-1-2 / NF EN 60601-1-1



Dealer's stamp

Owandy

6, allée Kepler 77420 Champs sur Marne France

Tel: +33 (0)1 64 11 18 18 Fax: +33 (0)1 64 11 18 10 Email: info@owandy.com

www.owandy.com

DIGITAL SENSORS

PANORAMIC UNITS

CAMERAS

RADIOLOGY EQUIPMENTS

SOFTWARE